

TANK GAZOIL

LOCKABLE EQUIPMENT CABINET

Equipment and ports are secure and spills are contained. Secure hose access enables fuelling while cabinet is locked.

CORNER BRACKETS

Liftable by crane and easily stackable: two high full and three high empty.

GALVANISED FRAME

Strong, durable and secure structure with added protection from bumps and scratches.

110% BUNDED

Built-in, weather proof secondary containment eliminates the need for drip trays.

REMOVABLE INNER TANK

For routine cleaning, maintenance and inspection.

INTERNAL BAFFLES

Designed to maximise stability when handling the tank full of fuel.

FOUR WAY FORKLIFT POCKETS

Quick and easy manoeuvring and mobility.





Ideal uses and applications

ONSITE FUEL SUPPLY

Easily refuel machinery on site when needed and cut back on fuel delivery waiting times.

FUEL TRANSPORT

Meeting multiple worldwide transport regulations, he can transport fuel safely anywhere you need it.

GENERATOR AND AUXILIARY EQUIPMENT

fuel tanks have the ability to quickly and efficiently connect to three diesel powered pieces of equipment and refuel equipment via pump at the same time.

Models and capabilities



SPECIFICATIONS

Capacity (Nominal / safe fill)	940 / 910 litres	2,048 / 1,970 litres	2,975 / 2,885 litres
Dimensions (L x W x H)	1,132 x 1,132 x 1,294mm	2,264 x 1,132 x 1,294mm	2,264 x 1,500 x 1,294mm
Weight (empty / full)	457 / 1,256kg	780 / 2,520kg	1,062 / 3,590kg
Design approvals	UL142, CAN/ULC-S601, UN-IBC, AS-1692 2006, ADG, VLAREM, KIWA		